

MU02I EIT Multiplexer



Outline :

MU02I EIT multiplexer is an enhanced TS multiplexer with EIT multiplexing function for digital TV broadcasting head-end system. EIT multiplexer has all the functions of normal TS multiplexer, including program multiplexing, PSI/SI editing, etc. It has 12 ASI input ports, 2 two separate ASI output ports and 2 gigabits IP output ports. Different from normal TS multiplexer, EIT multiplexer can not only multiplex programs' video, audio, PCR PIDs, but also multiplex the PIDs of program' s EIT table (event information table). When user selects the needed programs and give them to the output, The EIT table PIDs will automatically go to the output together with the programs' PIDs such as video, audio, PCR, ect. EIT table is the core part of EPG system of Digital TV Broadcasting. In Comparison with normal EPG system architecture, this facility largely gives the convenience to users who want to have EPG service to their Digital Head-end System. It doesn' t require EPG server, EPG Database, and day after day painstaking Database maintenance. The reason is most of TS from satellite has related EIT table (EPG information) already.



Features:

- 12 ASI inputs
- Two separate multiplexing ASI outputs, maximum code rate up to 215Mbps
- Two separate gigabit IP outputs as mirror of ASI outputs
- EIT automatically multiplexing with other program' s PID support
- PCR correction automatically support
- Local and Remote network management support



Specifications:

MPEG-2 TS Input	Supporting both packet and byte mode TS input	
	Supporting 188/204Byte transmission stream packet	
	12 ASI inputs	
	ASI input connector: BNC, impedance 75Ω	
ASI Output	Two separate ASI outputs	
	Maximum code rate: 215Mbps	
IP Output	Two separate gigabit outputs	
	Maximum output code rate: 215 Mbps	
	UDP output, unicast and multicast support	
Miscellaneous	Size	44mm X 482mm X 410mm
	Environment	0~45°C(operation); -20~80°C(storage)
	power	220VAC±10%, 50Hz, 25W