

IR41-S 4 in 1 Satellite Receiver



Overview:

IR41-S 4 In and 4 Out Satellite Receiver is a cost-effective receiver with high integration, which is newly developed by Telecast. The greatest feature of this product is that it has integrated four independent satellite receivers in one standard 1U case. Each satellite receiver has its own outputs of composite video, audio and ASI. They can work independently, and will not affect each other. This kind of design has optimized the function and structure greatly, and has saved some equipments, transportation cost, rack space and power consumption. It provides more convenience to user in operation.



Main Features:

1. 4 in 1 design, more compact structure
2. Completely compatible with MPEG2, DVB-S.
3. Satellite and transponder information editable
4. Play specified system when power on
5. Support OSD teletext (DVB ETS 300 706) and caption
6. Support PAL and NTSC TV standards
7. Automatic save for the last channel
8. User-friendly interface and easy operating menu system
9. Adopt 19' standard plug-in structure, flexible in use, save space effectively and lower the cost

10. LED display, operate with key



Technical Specification:

» Signal Input	» RF IN (F connector)	
» Receiving Level	» -65~-25dBm	
» Receiving Frequency	» 950~2150MHz	
» Symbol Rate	» 2~45Msps	
» FEC	» 1/2, 2/3, 3/4, 5/6, 7/8	
» Video Output	» CVBS×4 (RCA port)	
» Audio Output	» 4 channels audio outputs (RCA port), Left/Right channels	
» TS Output	» ASI×8 (BNC port)	
» System	» LED display, operate with key	
	» Chinese/English operating interface	
» Universal Attributes	» Dimension	» 482mm×370mm×44mm
	» Weight	» 3.6kg
	» Temperature	» 0~45 (operating), -20~80 (storage)
	» Power Supply	» AC 110~220V, 50/60Hz
	» Power Consumption	» 19.8W