

TL-47-H DVB-S SD MPEG-2 Set-Top-Box



DVB-S SD MPEG-2:

SOLUTION 1: ALI3328F+CE5039/RDA5812/AV2026

Support up to 1000 TPS, 2500 channels.

RF modulator (CH21-CH69)

256 colors on screen display OSD

SOLUTION 2: GX6101D+RDA5812/AV2026

Support up to 3000 TPS, 5000 channels

16:9 wide screen, 4:3 letter box, 4:3 pan scan

FEATURES

Fully DVB-S MPEG2 compliant

950-2150MHz input frequency .2-45Mb/s symbol rate.

22k Tone. Diseqc1.0, 1.2 support

Automatic blind scan
3 operation mode (Digital TV, Digital Radio, Favorite)
Scart video output
RF out .channel 11
Up to 9 pictures on screen
Multi-language, default English
Automatic PAL/NTSC conversion
Software upgrade through RS232

SOLUTION 3: ALI3329D+CE5039

Support up to 1000 TPS, 2500 channels.
Support Telecast CAS
Up to 9 pictures on screen

SOLUTION 4: GX6108+RDA5812

Support up to 2000 TPS, 5000 channels
Support Telecast CAS
Time shift function
Up to 16 picture on screen most.
Timer function support-wakeup time

SOLUTION 5: SUNPLUS1002A+SP6610+CE5039

Support up to 2000 TPS, 2000 channels
Timer function support-wakeup time
Native 32 Games.

FEATURES

Fully DVB-S MPEG2 compliant
950-2150MHz input frequency .2-45Mb/s symbol rate.
22k Tone. Diseq1.0, 1.2 support
Automatic blind scan
USB 2.0 for PVR Media Player & Software update
Disk manager

3 operation mode (Digital TV, Digital Radio, Favorite)

256 colors on screen display OSD

Scart video output

RF out .channel 11

RF MODULATOR(CH21-CH69)

SPDIF OUT

Electronic Program Guide(EPG)

Teletext and subtitle support

Multi-language, default English

Automatic PAL/NTSC conversion.

SOLUTION 6:ALI3329+CE5039/RDA5812

Support up to 1000 TPS. 2500 channels.

BISS function

Twin Protocol function

256 colors on screen display OSD

RF Modulator(CH21-CH69)

SOLUTION 7:GX6101+RDA5812

Support up to 3000 TPS, 5000 channels

BISS function

Twin Protocol function

16:9 wide screen, 4:3 letter box, 4:3 pan scan.

SOLUTION 8:ALI3329C+CE5039

Support up to 1000 TPS, 2500 channels

Electronic Program Guide(EPG)

Teletext and subtitle support

Support Telecast CAS

RF Modulator(CH21-CH69)

16:9 wide screen, 4:3 letter box, 4:3 pan scan.

256 colors on screen display OSD

FEATURES

Fully DVB-S MPEG2 compliant
950-2150MHz input frequency .2-45Mb/s symbol rate.
22k Tone.Diseqc1.0,1.2 support
Automatic blind scan
3 operation mode(Digital TV,Digital Radio,Favorite)
Scart video output
RF out channel 11
Up to 9 pictures on screen
Multi-language.default English
Automatic PAL/NTSC conversion
Software upgrade through RS232
OTA function



Overview:

HD(720P)
USB 2.0
Real Player
Multimedia player
Free To Air or embeded Telecast CAS



Features:

DVB-S & MPEG-2 compliant
SCPC & MCPC receivable from C/Ku-Band satellite
700 channels 1000TP memory space.
950-2150MHz input frequency.
Wide symbol rate 1-45Mbps
DISEQC1.2, DISEQC 1.0, TONE(22KHZ)and LNB Switching support

Electronic Program Guide(EPG),Tele-text and Subtitle Support.

Software upgreat from USB by the U-DISK or CARD

CVBS/L/R & Y Pb X 6 RCA

USB 2.0

Multimedia PLAYER-USB and SD CARD Reader

Media Support: Video-*.rm*.rmvb*.mpg*.avi

Audio-*.mp3*.wav*.wma

Photo-*.jpg*.bmp



DVB-S (AMLOGIC) CPU:AML8213 RAM:256M ROM:64M