

TL-62 DVB-S2 SD MPEG-4/H.264Set-top-Box



DVB-S2 SD MPEG-4/H.264:

SOLUTION 1:AL13381R+M3501+AV2011

Support up to 1000 TPS.2000 channels.

Support Telecast CAS

SOLUTION 2:AMLOGIC8626L+M88DS3002+YORP7306

Support up to 2000 TPS.4000 channels

Support Telecast CAS

Real Player .MKV player

Y Pb Pr out.support 720p

SOLUTION 3:GX3113B+GX1131+AV2011

Support up to 2000 TPS.3000 channels

Support Telecast CAS

Time shift function

Time function support-wakeup time

SOLUTION 4:Mstar7823+AV2108+YORP7306

Support up to 2000 TPS. 4000 channels

Support Telecast CAS

Y Pb Pr out

HDMI support 1080i

FEATURES

Fully DVB-S/S2 MPEG2/MPEG4/H.264 compliant. support SD

950-2150MHz input frequency 2-45Mb/s symbol rate.

22K Tone ,Diseqc 1.0 ,1.2 and USALS support

Automatic blind scan

USB 2.0 for PVR media player & software update

480i , 480P, 576i, 576P, support

16:9wide screen 4:3 letter box .4:3 pan scan

one scart

dolby

spdif

Electronic Program Guide(EPG)

Teletext and subtitle support

Multi-language. default English

automatic PAL\NTSC conversion.

SOLUTION 5 AMLOGIC8626H+AV2108+GAIA20R

Support up to 1000 TPS. 4000 channels

Support Telecast CAS

Real player .MKV player

Ethernet or WIFI function

SOLUTION 6 Mstar7821+M88DS3002+SHARP7306

Support up to 2500 TPS. 5000 channels

Support Telecast CAS

SOLUTION 7 Mstar7828+M88DS3002+SHARP7306

Support up to 2500 TPS, 5000 channels

FTA

FEATURES

Fully DVB-S/S2 MPEG2/MPEG4/H.264 compliant. support HD
950-2150MHz input frequency 2-45Mb/s symbol rate.
22K Tone ,Diseqc 1.0 ,1.2 and USALS support
Automatic blind scan
USB 2.0 for PVR media player & software update
High Definition media interface(HDMI)Version 1.3
576i,576P,720i,720P,1080i support
16:9wide screen 4:3 letter box .4:3 pan scan
Electronic Program Guide(EPG)
Teletext and subtitle support



Overview:

Full HD(1080P)
USB 2.0
PVR function via USB
Multimedia Player
Free To Air or Embeded TELECAST CAS



Features:

Support HDD
MPEG1/2/4,H.264 & Fully DVB compliant
5000 channels of TV&Radio
SCPC & MCPC receivable form C/Ku-Band satellites
950-2150MHz input frequency.
Diseqc1.0,1.2 and 22KHz tone supported.

Multiple language. default English.

Auto PAL\NTSC detection

Aspect Ratio:4:3 & 16:9

Software upgreat via USB

CVBS/L/R & YPbPr x 6 RCA

S/PDIF x 1(Digital Audio out)

HDMI x 1

USB 2.0

Multimedia support

Video(.avi,.mpg,.dat,.vob,.div,.mov,.mkv,.mjpeg,.ts,.trp.)

Audio(.wma,.mp3,.m4a)

Photo(.jpg,.bmp,.png)

DVB-S2 (MSTAR)

CPU:MSD7828

RAM:1G

ROM:64M

