

TL-62 ISDB-T HD MPEG-4/H.264 Set-top-Box



ISDB-T HD MPEG-4/H.264:

SOLUTION:MSD7828L+DIB8096

Fully ISDB-T MPEG4/H.264 compliant, support HD.

177.143-803.143MHz input frequency.

OFDM demodulation, 6MHz Bandwidth.

Support up to 4000 channels.

Automatic search & Manual search.

USB 2.0 for PVR, Media Player & Software update.

16:9 wide screen, 4:3 letter box , 4:3 pan scan.

High Definition Media interface (HDMI), Version 1.3.

576i , 576P, 720I, 720P, 1080i, support

YPbPr out.

DOLBY.

SPDIF.

Electronic Program Guide (EPG)

Teletext and Subtitle support
Muti_language, default English
Automatic PAL/NTSC conversion



Overview:

TL-62
Full HD(1080P)
USB 2.0
PVR function via USB
Multimedia Player
Free To Air
Embeded TELECAST CAS



Features:

Support HDD
1000 channels of TV&Radio
Frequency range Ch.7(177.143MHz)-Ch69(803.143MHz)Bandwidth 6MHz
Fully compliant to MPEG-1/2/4、H.264 & ISDB-T compliant.
Support TELETEXT, SUBTITLE function.
Auto search, manual search function.
Advance program management functions. Favorite, move, lock, rename, arrange, delete programs.
Timer: On timer/ Off timer/ Sleep timer.
Multiple language, default English.

Auto PAL-M/NTSC detection

Aspect Ratio:4:3 &16:9

Software upgreat via USB

CVBS/L/R & YPbPr x 6 RCA

S/PDIF x 1(Digital Audio out)

HDMI x 1

USB 2.0

Multimedia support

Video(.avi,.mpg,.dat,.vob,.div,.mov,.mkv,.mjpeg,.ts,.trp.)

Audio(.wma,.mp3,.m4a)

Photo(.jpg,.bmp,.png)

ISDB-T (MSTAR) CPU:MSD7828 RAM:1G ROM:64M